

## RAZORWELD ARC 160 PFC



### HD Backlit Interface

This next generation interface panel is bright and easy to read in any environment.

### Power Factor Correction (PFC)

PFC gives you maximum electrical efficiency. It automatically compensates for any voltage fluctuation, and PFC is also designed to be generator friendly.

### Advanced MMA Features

The RAZOR ARC 160 PFC features Anti-Stick technology, as well as adjustable Arc Force and Hot Start functionality. These features are designed for improving weld quality and ease of use.

### 10A Plug

A 10 AMP power plug can be used on any domestic outlet. It's perfect for the DIY home handyman or the professional welder looking for a machine that can be used almost anywhere.

### DC Lift Arc TIG

Lift Arc ignition allows the arc to be started easily in DC TIG by simply touching the tungsten to the workpiece and lifting it up to start the arc. This stops the tungsten tip sticking to the workpiece and breaking the tip from the tungsten electrode.

### Optional Remote Control

Upgrade your machine with a handy remote control. Both a wired and wireless controller are available.

### Smart Fan

Smart Fan diminishes noise, saves power, helps reduce energy costs, and minimises the number of contaminants being pulled through the machine.

### Lightweight & Portable

Weighing just 7.2kg, the RAZOR ARC 160 PFC is ready to go anywhere you need it.

## RAZORWELD ARC 200 PFC



### HD Backlit Interface

This next generation interface panel is bright and easy to read in any environment.

### Power Factor Correction (PFC)

PFC gives you maximum electrical efficiency. It automatically compensates for any voltage fluctuation, and PFC is also designed to be generator friendly.

### Advanced MMA Features

The RAZOR ARC 200 PFC features Anti-Stick technology, as well as adjustable Arc Force and Hot Start functionality. These features are designed for improving weld quality and ease of use.

### Optional Remote Control

Upgrade your machine with a handy remote control. Both a wired and wireless controller are available.

### DC Lift Arc TIG

Lift Arc ignition allows the arc to be started easily in DC TIG by simply touching the tungsten to the workpiece and lifting it up to start the arc. This stops the tungsten tip sticking to the workpiece and breaking the tip from the tungsten electrode.

### Smart Fan

Smart Fan diminishes noise, saves power, helps reduce energy costs, and minimises the number of contaminants being pulled through the machine.

### Lightweight & Portable

Weighing just 7.6kg, the RAZOR ARC 200 PFC is ready to go anywhere you need it.

# Machine Specifications

## RAZORWELD ARC 160 PFC

### Technical Data

Parameter	Values
SKU	XA-RZARC160PFC
Primary Input Voltage	240V Single Phase
Supply Plug	10 AMP
I <sub>eff</sub> (A)	10
Rated Output	20A/20.8V - 160A/26.4V
No Load Voltage (V)	78
Protection Class	IP23S
Insulation Class	H
Minimum Generator (kVA)	9.0
Dinse Connector	35/50
Standard	AS/NZ60974-1
MMA Weld Material type	Mild Steel, Stainless Steel, Cast Iron
TIG Weld Material type	Mild Steel, Stainless Steel, Copper, Silicon Bronze
Warranty (Years)	5

### STICK Specifications

Parameter	Values
STICK Welding Current Range	20-160A
STICK Duty Cycle @ 40°C	20% @ 160A 60% @ 93A 100% @ 72A
STICK Electrode Range	2.5-4.0mm
STICK Welding Thickness Range	2-10mm

### TIG Specifications

Parameter	Values
TIG Function Type	DC Lift Arc
TIG Welding Current Range	10-160A
TIG Duty Cycle @ 40°C	35% @ 160A 60% @ 123A 100% @ 95A
TIG Welding Thickness Range	1-6mm

### Size & Weight

Parameter	Values
Dimensions (mm)	413×150×311 mm
Weight (kg)	7.2kg

## RAZORWELD ARC 200 PFC

### Technical Data

Parameter	Values
SKU	XA-RZARC200PFC
Primary Input Voltage	240V Single Phase
Supply Plug	15 AMP
I <sub>eff</sub> (A)	14.9
Rated Output	20A/20.8V - 200A/28V
No Load Voltage (V)	78
Protection Class	IP23S
Insulation Class	H
Minimum Generator (kVA)	9.0
Dinse Connector	35/50
Standard	AS/NZ60974-1
MMA Weld Material type	Mild Steel, Stainless Steel, Cast Iron
TIG Weld Material type	Mild Steel, Stainless Steel, Copper, Silicon Bronze
Warranty (Years)	5

### STICK Specifications

Parameter	Values
STICK Welding Current Range	20-200A
STICK Duty Cycle @ 40°C	25% @ 200A 60% @ 129A 100% @ 100A
STICK Electrode Range	2.5-4.0mm
STICK Welding Thickness Range	2-12mm

### TIG Specifications

Parameter	Values
TIG Function Type	DC Lift Arc
TIG Welding Current Range	10-200A
TIG Duty Cycle @ 40°C	25% @ 200A 60% @ 129A 100% @ 100A
TIG Welding Thickness Range	1-8mm

### Size & Weight

Parameter	Values
Dimensions (mm)	413×150×311 mm
Weight (kg)	7.6kg